

## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CONATHANE® EN-1556 Part A Urethane Prepolymer

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Casting Resin

#### 1.3 Details of the supplier of the safety data sheet

Company : ELANTAS PDG, INC.  
North 2nd Street 5200  
63147 St. Louis

Telephone :  
Telefax :

Information : Todd Thomas, Manager Regulatory Affairs  
Telephone : (314)621-5700  
Telefax :  
Todd.Thomas@altana.com

#### 1.4 Emergency telephone number

GBK Gefahrgutbuero GmbH, Tel. +49 6132 84463

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 1	H330: Fatal if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H351 Suspected of causing cancer.

Precautionary statements

: **Prevention:**  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P284 Wear respiratory protection.  
**Response:**  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous components which must be listed on the label:

- 584-84-9 4-methyl-m-phenylene diisocyanate
- 91-08-7 2-methyl-m-phenylene diisocyanate

### 2.3 Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Isocyanate Prepolymer

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
4-methyl-m-phenylene diisocyanate	584-84-9 209-544-5	Carc. 2; H351 Acute Tox. 1; H330	>= 10 - < 12,5

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

	01-2119486974-18	Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Aquatic Chronic 3; H412	
2-methyl-m-phenylene diisocyanate	91-08-7 202-039-0	Carc. 2; H351 Acute Tox. 2; H330 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed**

None known.

## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Prevent unauthorized access. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Other data : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
4-methyl-m-phenylene diisocyanate	584-84-9	TWA	0,02 mg/m3 (NCO)	GB EH40
Further information	Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers			

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

	<p>who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma. The identified substances are those which: - are assigned the risk phrase 'R42: May cause sensitisation by inhalation'; or 'R42/43: May cause sensitisation by inhalation and skin contact' or - are listed in section C of HSE publication 'Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma' as updated from time to time, or any other substance which the risk assessment has shown to be a potential cause of occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.</p>			
	<table border="1"> <tr> <td data-bbox="470 1218 635 1272">STEL</td> <td data-bbox="639 1218 1201 1272">0,07 mg/m3 (NCO)</td> <td data-bbox="1206 1218 1386 1272">GB EH40</td> </tr> </table>	STEL	0,07 mg/m3 (NCO)	GB EH40
STEL	0,07 mg/m3 (NCO)	GB EH40		
Further information	<p>Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma. The identified substances are those which: - are assigned the risk phrase 'R42: May cause</p>			

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

	sensitisation by inhalation'; or 'R42/43: May cause sensitisation by inhalation and skin contact' or - are listed in section C of HSE publication 'Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma' as updated from time to time, or any other substance which the risk assessment has shown to be a potential cause of occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.			
2-methyl-m-phenylene diisocyanate	91-08-7	TWA	0,02 mg/m3 (NCO)	GB EH40
Further information	Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma. The identified substances are those which: - are assigned the risk phrase 'R42: May cause sensitisation by inhalation'; or 'R42/43: May cause sensitisation by inhalation and skin contact' or - are listed in section C of HSE publication 'Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma' as updated from time to time, or any other substance which the risk assessment has shown to be a potential cause of occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.			
		STEL	0,07 mg/m3 (NCO)	GB EH40
Further information	Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. 54 Substances that can cause occupational asthma should be			

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

	<p>distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified asthmagens or respiratory sensitisers., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma. The identified substances are those which: - are assigned the risk phrase 'R42: May cause sensitisation by inhalation'; or 'R42/43: May cause sensitisation by inhalation and skin contact' or - are listed in section C of HSE publication 'Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma' as updated from time to time, or any other substance which the risk assessment has shown to be a potential cause of occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma.</p>
--	--

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
4-methyl-m-phenylene diisocyanate	584-84-9	urinary diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	Post task	GB EH40 BAT
2-methyl-m-phenylene diisocyanate	91-08-7	urinary diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	Post task	GB EH40 BAT

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

4-methyl-m-phenylene diisocyanate : End Use: Workers  
 Exposure routes: Inhalation  
 Potential health effects: Acute systemic effects, Acute local effects  
 Value: 0,14 mg/m3  
 End Use: Consumers  
 Exposure routes: Inhalation  
 Potential health effects: Long-term systemic effects, Long-term local effects  
 Value: 0,035 mg/m3

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

4-methyl-m-phenylene diisocyanate : Fresh water  
 Value: 0,0125 mg/l  
 Marine water  
 Value: 0,00125 mg/l  
 Sewage treatment plant  
 Value: > 1 mg/l



## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

Intermittent releases  
Value: 0,125 mg/l  
Soil  
Value: > 1 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

#### Environmental exposure controls

- General advice : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : > 201 °F  
Method: No information available.  
Information taken from reference works and the literature.
- Evaporation rate : No data available
- Upper explosion limit : No data available

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1,05 g/cm <sup>3</sup> (25 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 22 mm <sup>2</sup> /s (40 °C)

**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : No decomposition if stored and applied as directed.

**10.4 Conditions to avoid**

Conditions to avoid : No data available

## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

### 10.5 Incompatible materials

### 10.6 Hazardous decomposition products

Carbon monoxide in a fire., Nitrogen oxides in a fire., Isocyanates

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: 0,47 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

##### Components:

#### **4-methyl-m-phenylene diisocyanate:**

Acute oral toxicity : LD50 (Rat, male): 5.110 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9.400 mg/kg  
Method: OECD Test Guideline 402

#### Skin corrosion/irritation

##### Product:

Remarks: May irritate skin.  
May cause skin irritation and/or dermatitis.

#### Serious eye damage/eye irritation

##### Product:

Remarks: May cause irreversible eye damage.

#### Respiratory or skin sensitisation

##### Product:

Remarks: Causes sensitisation.

#### Further information

##### Product:

Remarks: No data available

## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Components:**

**4-methyl-m-phenylene diisocyanate:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 133 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 12,5 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : ErC50 (Chlorella vulgaris (Fresh water algae)): 4.300 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- Toxicity to daphnia and other : NOEC: 1,1 mg/l  
aquatic invertebrates : Exposure time: 21 d  
(Chronic toxicity) : End point: Reproduction  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
GLP: yes

#### 12.2 Persistence and degradability

**Components:**

**4-methyl-m-phenylene diisocyanate:**

- Biodegradability : Result: Not biodegradable

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

- Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Other adverse effects

**Product:**

- Additional ecological : Remarks: No data available  
information

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

- Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14: Transport information**

**14.1 UN number**

- ADR/RID : UN 2206  
IMDG : UN 2206  
IATA : UN 2206

**14.2 UN proper shipping name**

- ADR/RID : ISOCYANATES, TOXIC, N.O.S.  
(Toluene diisocyanate)
- IMDG : ISOCYANATES, TOXIC, N.O.S.  
(TOLUENE DIISOCYANATE)  
Marine Pollutant (TOLUENE DIISOCYANATE)
- IATA : Isocyanates, toxic, n.o.s.  
(Toluene diisocyanate)

**14.3 Transport hazard class(es)**

- ADR/RID : 6.1  
IMDG : 6.1  
IATA : 6.1

**14.4 Packing group**

- ADR/RID  
Packing group : II  
Classification Code : T1  
Hazard Identification Number : 60  
Labels : 6.1  
Tunnel restriction code : D/E
- IMDG  
Packing group : II

## CONATHANE® EN-1556 Part A Urethane Prepolymer

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

Labels : 6.1  
EmS Code : F-A, S-A

### IATA

Packing instruction (cargo aircraft) : 662  
Packing instruction (passenger aircraft) : 654  
Packing instruction (LQ) : Y641  
Packing group : II  
Labels : Toxic

### 14.5 Environmental hazards

#### ADR /RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
H1	ACUTE TOXIC	5 t	20 t
26	Toluene diisocyanate	10 t	100 t

### 15.2 Chemical safety assessment

## SECTION 16: Other information

### Full text of H-Statements

H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.

**CONATHANE® EN-1556 Part A Urethane Prepolymer**

Product code: 000000000000124998

Version 1.0 SDB\_GB

Revision Date 13.03.2018

Print Date 13.03.2018

- H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 : May cause respiratory irritation.
- H351 : Suspected of causing cancer.
- H412 : Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

- Acute Tox. : Acute toxicity
- Aquatic Chronic : Chronic aquatic toxicity
- Carc. : Carcinogenicity
- Eye Irrit. : Eye irritation
- Resp. Sens. : Respiratory sensitisation
- Skin Irrit. : Skin irritation
- Skin Sens. : Skin sensitisation
- STOT SE : Specific target organ toxicity - single exposure

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.