J-FOAM 7087 Part A

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product Name: J-Foam 7087 Part A

Chemical Name: Resin Blend

Supplier: Jacobson Chemicals Ltd

Unit 4

Newman Lane Industrial Estate

Alton Hants GU34 2QR 01420 86934 01420 549574

Fax: 01420 549574
E-mail: sales@jacobsonchemicals.co.uk

2. COMPOSITION

Telephone:

Substance:N/aSubstance Name:N/aEC Index No:N/aCAS Number:107-21-1EEC Number:N/a

Constituents EINECS No. Contents Symbol Risk

Ethanediol 203-473-3 5-10% Xn R22- Harmful if

swallowed.

3. HAZARD INDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

For further information, please refer to section 11.

This material has a flash point between 21°C and 55°C, but does not support combustion when tested in accordance with Schedule 2 or the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972. Therefore, whilst this product is not classified as flammable, this MSDS contains phrases to help make the user aware of potential flammability hazards.

J-FOAM 7087 Part A

4. FIRST AID MEASURES

Immediate medical attention:

Professional assistance from physician

required?

Ingestion:

No Yes

Inhalation: Move the exposed person to fresh air at once.

Perform artificial respiration if breathing has stopped. Keep the affected person warm and at

rest. Get prompt medical attention.

Skin Contact: Remove affected person from source of

contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if irritation persists

after washing.

Eye Contact: Make sure to remove any contact lenses from the

eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues. Rinse mouth thoroughly. Immediately give a couple of glasses of water or milk, provided the

couple of glasses of water or milk, provided the victim is fully conscious. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort

continues.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Powder, foam or CO2. Larger fires: Water spray,

fog or mist.

Special fire fighting procedures: Move container from fire area if it can be done

without risk. No specific fire fighting procedure

given.

Unusual fire and explosion hazards: If heated, volume and pressure increases strongly,

resulting in explosion of container. May ignite if heated. Prolonged exposure to heat may lead to

formation of toxic gases.

Hazardous decomposition products: Fire or high temperatures create toxic

gases/vapour/fumes of carbon monoxide (CO),

carbon dioxide (CO2).

J-FOAM 7087 Part A

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin or inhalation of spillage,

dust or vapour.

Methods of Cleaning: Do not touch spilled material. Extinguish all

ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Cleanup personnel should use respiratory and/or liquid contact protection. Collect with absorbent, non-combustible material into suitable containers. Provide ventilation and confine spill; do not allow runoff to sewer. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. Do not contaminate water sources or

sewer.

7. HANDLING & STORAGE

Usage precautions: Avoid spilling, skin and eye contact. Do not use

contact lenses. Do not use in confined spaces without adequate ventilation and/or respirator. Static electricity and formation of sparks must be prevented. Eliminate all sources of ignition. Consider the use of intrinsically safe electrical equipment. Open containers carefully: risk of

pressure build up.

Storage: Ground container and transfer equipment to

eliminate static electric sparks. Keep in original container. Keep containers tightly closed. Keep in cool, dry, ventilated storage and closed containers. Store below 25°C. Keep away from

heat, sparks and open flame.

Storage criteria: Flammable liquid storage.

J-FOAM 7087 Part A

8. EXPOSURE CONTROLS

Ingredient Name	Cas No	STD	LT EXP (8hrs)	ST EXP (15 min)
Ethanediol	107-21-1	OES	52 mg/m³ (Sk)	104 mg/m³ (Sk)

OES: Occupational Exposure Standard. MEL: Maximum Exposure Limit

Take measures to prevent: N/a Exposure to control limits: N/a

Respiratory protection:All handling to take place in a well ventilated

area. Provide adequate general and local exhaust

ventilation.

Hand Protection: General guidance on hand protection. Chemical

resistance gloves required for prolonged or repeated contact. Protective gloves must be used if there is a risk of direct contact or splash. Use

gloves made of Nitrile or Neoprene.

Eye Protection: Wear splash proof eye goggles to prevent any

possibility of eye contact. Contact lenses should not

be worn when working with this chemical.

Skin Protection: Wear appropriate clothing to prevent any possibility

of skin contact.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance:Viscous. LiquidOdour:Mild (faint) AmineColour:Colourless, clear.

Viscosity: 800 - 1,000 m Pas @ 20°C

Specific Gravity: 0.95 - 1.05 @ 20°C

Flash Point: 34

Flash Point Method: CC (closed cup)

Volatile by Vol: <20

10. STABILITY & REACTIVITY

Stability: Normally stable. Avoid heat, sparks, flames. **Conditions to avoid:** Avoid heat, flames and other sources of ignition.

Avoid contact with acids.

Materials to avoid: Acids, oxidizing agents.

Hazardous decomposition products: Toxic gases/vapours/fumes of Carbon monoxide

(CO), Carbon Dioxide (CO2), Hydrocarbons.

Flammable gases/vapours.

J-FOAM 7087 Part A

11. TOXICOLOGICAL INFORMATION

Inhalation: Solvent vapours are hazardous and may cause

nausea, sickness and headaches.

Ingestion: May cause discomfort in swallowed.

Skin: Liquid may irritate skin.

Eyes: Spray and vapour in the eyes may cause irritation

and smarting.

Health Warnings:No known chronic or acute health risks.

12. ECOLOGICAL INFORMATION

Possible effects: N/a
Behaviour: N/a

Environmental fate: Not regarded as dangerous to the environment.

13. DISPOSAL CONSIDERATIONS

Disposal Methods: Dispose of in accordance with local authority

requirements. Do not allow runoff to sewer,

waterway or ground.

14. TRANSPORT INFORMATION

Special carriage precautions in carriage:

Classification data:

UN Number: 1993

Proper Shipping Name: Flammable liquid, N.O.S. (Methylal)

Additional Data: Class 3, Flammable liquids

IMO - Sea: Class 3, III ICAO - Air: N/a ADR - Road: Class 3, III

EmS No: 3-07

J-FOAM 7087 Part A

15. REGULATORY INFORMATION

Risk Phrases: R22 Harmful if swallowed.

Safety Phrases: U-6 Contains volatile blowing agent - Risk of

pressure build up.

UK Regulatory References:Health and Safety at Work Act 1974 **EC Directives:**Dangerous Preparations Directive 88/379

Statutory Instruments: Chemicals (Hazard Information and Packaging)

Regulations.

Guidance Notes: Occupational Exposure Limits EH40.

Isocyanates toxic hazards and precautions EH16.

CHIP for everyone HSG (108)

Baxenden Brochure Isocyanates & Polyurethanes -

Safety advice.

16. OTHER INFORMATION

a) Training needs: For further information contact our office.

b) Recommended uses and

restrictions:

c) Further references:

d) Key data sources:Manufacturer's data.

The data contained in this Safety Data Sheet has been supplied as required, by the Chemicals (Hazard Identification and Packaging) Regulations 1994, as amended, for the purposes of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided.

Please ensure that it is passed to the appropriate person in your company, who is capable of acting on the information.

NOTE:

This data sheet does not constitute a user's assessment of workplace risk as required by HSW Act, COSHH, Management of Health and Safety at Work regulations, or other Health & Safety at Work regulations.